Tables for echocardiography

3-sectioned table for echocardiography with hydraulic height adjustment ... for examination, treatment ...

Model 2552-00XL/H white powder coated (RAL 9010) Model 2552-03XL/H white aluminium powder coated (RAL 9006) Model 2552-04XL/H grey aluminium powder coated (RAL 9007)



Available as an option (see pricelist for additional options) Mobility





Art. no. 1180N Movable on twin castors, Ø 100 mm with central lock, basic height +20 mm






Art. no. 1270K / 1280K Paper roll holder, mounted under head part (not protruding), for width 700 mm / 800 mm

Add-on elements





(protruding: 70 mm),

Art. no. 1410 1 piece of side rail, length: 350 mm

Storage basket









Art. no. 1040 1 side guard tiltable, chromium-plated, completely made of steel tube, length: 700 mm

Art. no. 2552-800 Width of upholstery: 800 mm

Art. no. 1770 / 1780 Soft covering for pleasant resting comfort, for width 700 mm / 800 mm, thickness 80 mm

Art. no. 1772 / 1782 Upholstery medium-soft (cold foam cover), for width 700 mm / 800 mm, thickness 70 mm

All pictures: Model 2552-00XL/H with options: Movable on twin castors with central lock (1180N), paper roll holder (1270K); upholstery colour 64-711 ash grey

Germai manufacture

3



Upholstery:

- Table not movable, including height adjustment screws to compensate for uneven ground
- In head part: Cut-out for echocardiography and upholstery part to close (in patient supine position left)
- Pedals for foot-controlled height positioning on both sides of the table
- Dewert-hygiene-equipment











Art. no. 1080-50 chromium-plated, completely made of steel

Wall protection bumpers



Art. no. 1170 1 wall protection bumper Ø 150 mm













- Skai® Pandoria Plus with velvet-smooth surface ٠
- Skai® Toronto EN with innovative staynu-technology





- Head part stepless upwards (+50°) adjustable by gas spring
- Length head part: 800 mm

Lying surface 3-sectioned:


- In head part: Cut-out for echocardiography and upholstery part to close,
- in patient supine position left, measures: L. 300 mm x W. 250 mm
- Fixed middle part, length: 300 mm
- Foot part stepless upwards (+30°) adjustable by gas spring ٠
- Length foot part: 850 mm
- Upholstery thickness: 60 mm •

Technical data:

- Manual foot operated height adjustment: 560 mm to 980 mm by hydraulic pump, pressure capacity of 10000 N
- Width of lying surface: 700 mm, optional 800 mm •
- Length of lying surface: 1950 mm •
 - Load capacity: 250 kg; according to IEC 60601 tested with fourfold static load

Design:


2 different variants for artificial leather eligible for upholstery covering:







Paper roll holder







1 side guard lateral lowerable, tube, length: 1060 mm, length on cut-out side: 820 mm





Art. no. 1185 Movable on comfort twin castors, Ø 125 mm with central lock. basic height + 50 mm





Art. no. 1045N Wheel-lifting/fixing mechanism with 4 foot levers for controlled lowering

Art. no. 1270F / 1280F Paper roll holder, mounted at foot part

for width 700 mm / 800 mm







Art. no. 1005 1 side guard to fit on side rail, with attachment clamp, chromium-plated, length: 800 mm

Upholstery options

Updated 04.2023 01 changes concerning the technical data are subject to change